



P.O. Box 754,
Edinboro, PA 16412-0754
sales@beaconlubricants.com

toll free: (877) 734-7334
phone: (814) 734-7535
fax: (814) 734-3460

technical data sheet

Beacon Signal Vac AXT Pump Oils

Product Application:

Beacon Signal Vac AXT Pump Oils are industrial grade compressor/vacuum lubricants specially formulated from high VI paraffinic and with a blend of polyalphaolefin base stocks.

Beacon Lubricants Signal Vac AXT Pump Oils are characterized by outstanding rust protection, low deposit formation, excellent demulsibility, and low air entrainment, excellent anti-foam properties. Recommended drain intervals in excess of 8,000 hours or more under normal operating conditions.

Package Size:

Bulk, Drums, Pails

Meets or Exceeds the following Specifications:

Cincinnati Milacron Heat Test A
Abex-Denison HF-1
Cincinnati Milacron P-38, P-54, P-57
Mil-H-17672D
General Electric GEK-32568
AGMA Specification for R&O Gear Oils
ASTM D-943 (5000 hours)

Typical Characteristics:

ISO GRADE	32	46	68	100	150
Gravity, Degrees API	30	30	32	30	29.5
AGMA Number	--	1	2	3	4
Viscosity Index (Min.)	140	145	155	170	180
Viscosity					
cSt @ 100 °C	5.4	6.5	8.4	11	14
cSt @ 40 °C	32.2	46	65	98	145
Flash Point, COC, °F	502	507	509	511	515
Pour Point, °F	-55	-45	-40	-40	-35