

20' STANDARD FLAT PANEL OFFSHORE CONTAINER

20' x 8' x 8'6" Standard Height - Flat Panel
 Double Cargo Doors on one end
 Painted Finish
 1/4" Side Wall Optional



CERTIFICATIONS

DNV 2.7-1 (DNV-ST-E271) Standard for Offshore Containers
 ISO 10855 International Standard for Offshore Containers and associated lifting sets
 In support of IMO MSC Circ 860
 CSC Convention for Safe Containers
 API / Shell OPS0055 by request
 Classification Society : Lloyd's Register (LR) or Det Norske Veritas (DNV)

DIMENSIONS (+/- 1/4")

	EXTERNAL	INTERNAL
Length	6058 mm 20'	5845 mm 19' - 2 2/16"
Width	2438 mm 8'	2218 mm 7' - 3 5/16"
Height	2591 mm 8'-6"	2218 mm 7' - 3 5/16"
Door Opening Width		2218 mm 7' - 3 5/16"
Door Opening Height		2198 mm 7' - 2 9/16"
Internal Cubic Capacity		29.4 M ³ 1038 FT ³



RATINGS (+/- 3%)

For Offshore / Sling Movement

Max Gross Weight	14,150 kg	31,200 lbs
Max Payload	10,000 kg	22,050 lbs
Tare Weight	4,150 kg	9,150 lbs

For Standard Cargo / Fork Lift / Top Lift Movement

Max Gross Weight	24,000 kg	52,910 lbs
Max Payload	19,850 kg	43,760 lbs
Tare Weight	4,150 kg	9,150 lbs

INCLUDES

- DNV Certified Wire Rope Lifting Sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

