

24' HALF HEIGHT - REMOVABLE SIDE OFFSHORE BASKET

24' x 8' x 4'2"

Removable Side Door

Hot Dip Galvanized or Painted Finish



CERTIFICATIONS

DNV 2.7-1 (DNVGL-ST-E271) Standard for Offshore Containers
ISO 10855 International Standard for Offshore Containers and associated lifting sets

In support of IMO MSC Circ 860

API / Shell OPS0055 by request

Classification Society : Lloyd's Register or Det Norske Veritas (DNV)

DIMENSIONS (+/- 1/4")

	EXTERNAL	INTERNAL
Length	7315 mm 24'	6991 mm 22'-11 4/16"
Width	2438 mm 8'	2114 mm 6'-11 4/16"
Height	1280 mm 4'-2"	857 mm 2'-9 12/16"
Door Opening Width		6000 mm 19'-8 4/16"
Internal Cubic Capacity		12.66 M ³ 447 FT ³



RATINGS (+/- 3%)

For Offshore / Sling Movement

Max Gross Weight	16,000 kg	35,280 lbs
Max Payload	11,850 kg	26,130 lbs
Tare Weight	4,150 kg	9,150 lbs

For Standard Cargo / Forklift Lift Movement

Max Gross Weight	16,000 kg	35,280 lbs
Max Payload	11,850 kg	26,130 lbs
Tare Weight	4,150 kg	9,150 lbs

INCLUDES

- DNV Certified Wire Rope Lifting Sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

