



P.O. Box 754,
Edinboro, PA 16412-0754
sales@beaconlubricants.com

toll free: (877) 734-7334
phone: (814) 734-7535
fax: (814) 734-3460

technical data sheet

Stoddard Solvent

Product Application:

Stoddard Solvent is used for a parts cleaner, paint thinner, charcoal starter, used in hand cleaners, asphalt cutbacks, and industrial cleaners

Package Size:

2.5 gallons, 5 gallon pail, 55 gallon drum

Typical Characteristics:

ASTM Method	Description	Specification		
		Minimum	Maximum	Typical
	LB/GAL	6.40	6.47	6.43
D4052	Gravity, API	50.4	52.3	51.4
D56	Flash Point, °F(°C)	105(41)		
D611	Aniline Point, °C			65
D1133	Kauri Butanol Value			32.52
D5949	Pour point, °C(°F)			-60 (-76)
D2622	Sulfur, WT %		0.0050	<0.0005
D156	Color, Saybolt			+30
D86	Distillation, °F			
	IBP			310
	5% 310			322
	50%			341
	95%			375
	EBP		410	393
D1319	Flour. Indicator Analysis			
	Aromatics, Vol %			10.5
	Olefins, Vol %			0.4
	Saturates, Vol %			89.1