

14' HALF HEIGHT OFFSHORE BASKET

14' x 8' x 4'1"

Side Swing Door

Hot Dip Galvanized or Painted Finish



CERTIFICATIONS

DNV 2.7-1 (DNVGL-ST-E271) Standard for Offshore Containers

ISO 10855 International Standard for Offshore Containers and associated lifting sets

In support of IMO MSC Circ 860

API / Shell OPS0055 by request

Classification Society : Lloyd's Register or Det Norske Veritas (DNV)

DIMENSIONS (+/- 1/4")

	EXTERNAL	INTERNAL
Length	4268 mm 14'	3944 mm 12'-11 17/64"
Width	2438 mm 8'	2114 mm 6'-11 7/32"
Height	1255 mm 4'-1"	934 mm 3'-0 49/64"
Door Opening Width		2260 mm 7'-5 23/64"
Internal Cubic Capacity		7.78 M ³ 274 FT ³



RATINGS (+/- 3%)

For Offshore / Sling Movement

Max Gross Weight	12,100 kg	26,680 lbs
Max Payload	10,000 kg	22,050 lbs
Tare Weight	2,100 kg	4,630 lbs

For Standard Cargo / Forklift Lift Movement

Max Gross Weight	12,100 kg	26,680 lbs
Max Payload	10,000 kg	22,050 lbs
Tare Weight	2,100 kg	4,630 lbs

INCLUDES

- DNV Certified Wire Rope Lifting Sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

