20' HIGH CUBE - OFFSHORE REMOVABLE FRAME

20' x 8' x 9'6"

Hot Dip Galvanized or Painted Finish

CERTIFICATIONS

DNV 2.7-1 (DNVGL-ST-E271) Standard for Offshore Containers **ISO 10855** International Standard for Offshore Containers and associated lifting sets

In support of IMO MSC Circ 860

CSC: Convention for Safe Containers

API / Shell OPS0055 by request

Classification Society: Lloyd's Register or Det Norske Veritas (DNV)



DIMENSIONS (+/- 1/4")

	EXTERNAL	INTERNAL
Length	6058 mm 20'	5638 mm 18'-5 15/16'
Width	2438 mm 8'	2118 mm 6'-11 6/16"
Height	2896 mm 9'-6"	2513 mm 8'-2 15/16"

RATINGS (+/- 3%)

For Offshore / Sling Movement

 Max Gross
 25,000 kg
 55,115 lbs

 Max Payload
 19,900 kg
 43,872 lbs

 Tare Weight
 5,100 kg
 11,243 lbs

INCLUDES

- DNV Certified Wire Rope lifting sling
- Full Data Book
 - Electronic Mobilization Packet
- Original Certificates
- Delivery to your yard
- 16 built in lashing rings













