



P.O. Box 754,  
Edinboro, PA 16412-0754  
sales@beaconlubricants.com

toll free: (877) 734-7334  
phone: (814) 734-7535  
fax: (814) 734-3460

technical data sheet

## Signal Film 150

### Product Application:

Signal Film 150 is a full-bodied neutral mineral oil based rust preventative and penetrant lubricant developed for use as a corrosion protectant in automotive and commercial settings. Such as "oil undercoating."

This product utilizes the latest cutting edge technology in water impervious base stocks, rust and corrosion inhibitors and plasticized polymer tackifiers that allows for uniform film thickness and ease of application while leaving a tenacious protective film to any surface applied.

This durable product prevents and in many cases slows and halts oxidizing rust in the harshest of winter climates.

### Recommended methods of application:

- \*Air operated undercoating equipment
- \*Air less spray equipment
- \*Brush

### Theoretical Coverage:

- \*Average use is 1.0 – 1.5 gallons per average size vehicle.

### Typical Characteristics:

Specific Gravity @ 60 °F	.89
Flash Point	400 °F
Pour Point	10 °F
Appearance	Amber
Cure Time	1.0 Hour

### Clean up recommendations:

- \*Easily cleaned up with warm soapy water or mineral spirits

### Package Sizes Available:

2.5 gallon containers, 5 gallon pails, 55 gallon drums