


etched

ENGINEERED WOOD FOR WALLS & CEILINGS




JAMIE BECKWITH®
COLLECTION


1. PATTERNS



Pop




Shooter




Stitch




Off the Grid



Fret




Button




Oval



Ribbed



Chevron




Kuba



Chat




Rivet




rx


2. SPECIES



Quarter White Oak



Plain White Oak



Walnut

3. NAILHEADS


AVAILABLE FOR KUBA & RIVET PATTERNS ONLY:




Matte Gold



Nickel



Bronze



Smoke

4. STAINS


AVAILABLE ON WHITE OAK SPECIES




Polished Amber




Dolphin



Smokey Quartz



Black Onyx




Grey Moonstone




Pickled Pearl




Mist



Gris




Slate




Sapphire


AVAILABLE ON WALNUT SPECIES:



Polished Amber




Dolphin




Smokey Quartz




Black Onyx




Grey Moonstone



Pickled Pearl



Mist



Sapphire

SPECIFICATIONS

WOOD TILE CONSTRUCTION:

4mm wear layer over 9 ply substrate.
5/8" Thickness.

INSTALLATION:

Glue down. (See installation guidelines)

FIRE RATING:

Class C. (Class B available upon request)

BOX QUANTITY:

Varies by pattern

USAGE:

Warranted for Commercial or Residential walls & ceilings.
Not suitable for areas exposed to running water: inside showers, etc.
Not suitable for outdoor applications.

Not suitable for flooring.

LEADTIME:

6-8 weeks for production.

Expedited options available upon request.

STAINING SYSTEM:

Rubio Monocoat hard oil finish - no VOC.
Available unfinished.

LEED CREDITS:

2009 NC/CI MR Credit 5 - Regional Materials
2009 NC/CI IEQ Credit 4.1-4.4 - Low Emitting Finish

***This product may contribute to the achievement of LEED credits, although JBC makes no guarantees of representation of such.