



P.O. Box 754,  
Edinboro, PA 16412-0754  
sales@beaconlubricants.com

toll free: (877) 734-7334  
phone: (814) 734-7535  
fax: (814) 734-3460

safety data sheet

**Safety Data Sheet: Signal Cut 396**

**Revision Date: January 2<sup>nd</sup> 2024**

## SECTION 1

## PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT

**Product Name:** Signal Cut 396

**Product Description:** Base oil and Additives

**Intended Use:** Metal processing fluid

### COMPANY IDENTIFICATION

**Supplier:** Beacon Lubricants  
P.O Box 754  
Edinboro, PA 16412

**Emergency Telephone:** 1-877-734-7334 – Beacon Lubricants, Inc.

**Emergency Telephone:** 1-800-424-9300 (24 hours) – Chemtrec approval

Visit us at: [www.beaconlubricants.com](http://www.beaconlubricants.com)

## SECTION 2

## HAZARDS IDENTIFICATION

This material is not hazardous according to regulatory guidelines (M)SDS Section 15)

**Other hazard information:**

**HAZARD NOT OTHERWISE CLASSIFIED (HNOC):** None as defined under 29 CFR 1900. 1200.

### PHYSICAL / CHEMICAL HAZARDS

No significant hazards

### HEALTH HAZARDS

High-pressure injection under skin may cause serious damage. Mists may be irritating to the eyes, nose, throat and lungs. May be irritating to nose, throat, and lungs.

### ENVIRONMENTAL HAZARDS

No significant hazards.

**NFPA Hazard ID:** Health: 0 Flammability: 1 Reactivity: 0

**HMIS Hazard ID:** Health: 0 Flammability: 1 Reactivity: 0



**Note:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

**SECTION 3****COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Name</b>	<b>CAS #</b>	<b>Concentration*</b>
Fats and Glyceridic oils, animal, mixed with vegetable oils, sulfurized	68991-19-5	5-10%

**SECTION 4****FIRST AID MEASURES****INHALATION**

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

**SKIN CONTACT**

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

**EYE CONTACT**

Flush thoroughly with water. If irritation occurs, get medical assistance.

**INGESTION**

First aid is normally not required. Seek medical attention if discomfort occurs.

**SECTION 5****FIRE FIGHTING MEASURES**



P.O. Box 754,  
Edinboro, PA 16412-0754  
sales@beaconlubricants.com

toll free: (877) 734-7334  
phone: (814) 734-7535  
fax: (814) 734-3460

safety data sheet

## EXTINGUISHING MEDIA

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Inappropriate Extinguishing Media:** Straight streams of water

## FIRE FIGHTING

**Fire Fighting Instructions:** use large quantities of foam as it is partially destroyed by the product. Cool endangered containers with water spray.

## SECTION 6

## ACCIDENTAL RELEASE MEASURES

### NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800) 424-8802.

### PROTECTIVE MEASURES

Avoid contact with spilled material. See Section 5 for firefighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Service. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgement of the emergency responders.

For emergency responders: Respiratory protection: respiratory protection will be necessary only in special cases, e.g., formation of mists. half-face or full-face respirator with filter(s) for dust/organic vapor or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Work gloves that are resistant to hydrocarbons are recommended. Gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

## SPILL MANAGEMENT



**beacon**  
**lubricants**<sub>INC</sub>

P.O. Box 754,  
Edinboro, PA 16412-0754  
sales@beaconlubricants.com

toll free: (877) 734-7334  
phone: (814) 734-7535  
fax: (814) 734-3460

safety data sheet

**Land Spill:** Stop leak if you can do it without risk. Recover by pumping or with suitable absorbent.

**Water Spill:** Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

### ENVIRONMENTAL PRECAUTIONS

Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

## SECTION 7

## HANDLING AND STORAGE

### HANDLING

Avoid breathing mists or vapors. Avoid contact with skin. Avoid contact with eyes. Small metal particles from machining may cause abrasion of the skin and may predispose to dermatitis. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or ground procedures. However, bonding and ground may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance.

Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

**Static Accumulator:** This material is a static accumulator.

### STORAGE:

The container choice, for example storage vessel, may effect static accumulation and dissipation. Do not store in open or unlabeled containers. Keep away from incompatible materials.



P.O. Box 754,  
Edinboro, PA 16412-0754  
sales@beaconlubricants.com

toll free: (877) 734-7334  
phone: (814) 734-7535  
fax: (814) 734-3460

safety data sheet

## SECTION 8

## EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE LIMIT VALUES

**Exposure limits/standards for materials that can be formed when handling this product:** When mists/aerosols can occur the following is recommended: 5 mg/m<sup>3</sup> - OSHA PEL.

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

No biological limits allocated.

### ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions.

Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

### PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information of the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: Particulate air-purifying respirator approved for dust / oil mist is recommended.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published



**beacon  
lubricants** INC

P.O. Box 754,  
Edinboro, PA 16412-0754  
sales@beaconlubricants.com

toll free: (877) 734-7334  
phone: (814) 734-7535  
fax: (814) 734-3460

safety data sheet

literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacture for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include: No protection is ordinarily required under normal conditions of use.

**Eye Protection:** If contact is likely, safety glass with side shields are recommended. Chemical type goggles should be worn during misting operations.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include: No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taking to avoid skin contact.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

### Environmental Controls

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

## SECTION 9

## PHYSICAL AND CHEMICAL PROPERTIES

**Note:** Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the supplier for additional information.

### GENERAL INFORMATION

**Color:** Amber

**Odor:** Mild

**Odor Threshold:** N/D

### IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

**Relative Density (at 15°C):** 0.9

**Flammability (Solid, Gas):** N/A





**beacon**  
**lubricants** INC

P.O. Box 754,  
Edinboro, PA 16412-0754  
sales@beaconlubricants.com

toll free: (877) 734-7334  
phone: (814) 734-7535  
fax: (814) 734-3460

safety data sheet

**Flash Point [Method]:** 171°C (340°F) [ASTM D-92]

**Flammable Limits (Approximate volume % in air):** LEL: 0.9 UEL: 7.0

**Autoignition Temperature:** N/D

**Boiling Point / Range:** >200°C (392°F)

**Decomposition Temperature:** N/D

**Vapor Density (Air = 1):** > 1 at kPa (0.1 mm Hg) at 20°C

**Vapor Pressure:** < 0.013 kPa (0.1 mm Hg) at 20 °C

**Evaporation Rate (n-butyl acetate = 1):** N/D

**pH:** N/A

**Log Pow (n-Octanol/Water Partition Coefficient):** N/D

**Solubility in Water:** Negligible

**Viscosity:** > 15 cSt (15 mm<sup>2</sup>/sec) at 40°C | > 4.1 cSt (4.1mm<sup>2</sup>/sec) at 100°C

**Oxidizing Properties:** See Hazards Identification Section.

#### OTHER INFORMATION

**Freezing Point:** N/D

**Melting Point:** N/A

**Pour Point:** < 0°C (32°F)

**DMSO Extract (mineral oil only), IP-346:** < 3 % wt

## SECTION 10

## STABILITY AND REACTIVITY

**REACTIVITY:** See sub-sections below.

**STABILITY:** Material is stable under normal conditions

**CONDITIONS TO AVOID:** Excessive heat. High energy sources of ignition.

**MATERIALS TO AVOID:** Strong oxidizers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.

## SECTION 11

## TOXICOLOGICAL INFORMATION

### INFORMATION ON TOXICOLOGICAL EFFECTS

Hazard Class	Conclusion / Remarks
--------------	----------------------



P.O. Box 754,  
Edinboro, PA 16412-0754  
sales@beaconlubricants.com

toll free: (877) 734-7334  
phone: (814) 734-7535  
fax: (814) 734-3460

safety data sheet

<b>Inhalation</b>	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on the assessment of the components.
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures.
<b>Ingestion</b>	
Acute Toxicity: No end point date for material	Minimally Toxic. Based on assessment of components.
<b>Skin</b>	
Acute Toxicity: No end point date for material	Minimally Toxic. Based on assessment of components.
Skin Corrosion/Irritation: No end point data for material.	Negligible irritation to skin at ambient temperatures. Based on assessment of the components.
<b>Eye</b>	
Serious Eye Damage/Irritation: No end point data for material	May cause mild, short-lasting discomfort to eyes. Based on assessment of components.
<b>Sensitization</b>	
Respiratory Sensitization: No end point data for material	Not expected to be a respiratory sensitizer
Skin Sensitization: No end point date for material	Not expected to be a skin sensitizer. Based on assessment of the components.
<b>Aspiration:</b> Data available	Not expected to be an aspiration hazard. Based on physico-chemical properties of the materials.
<b>Germ Cell Mutagenicity:</b> No end point data for material	Not expected to be a germ cell mutagen. Based on assessment of the components.
<b>Carcinogenicity:</b> No end point data for material	Not expected to cause cancer. Based on assessment of the components.
<b>Reproductive Toxicity:</b> No end point data for material	Not expected to be a reproductive toxicant. Based on the assessment of the components
<b>Lactation:</b> No end point data for material	Not expected to cause harm to breast-fed children
<b>Specific Target Organ Toxicity (STOT)</b>	





P.O. Box 754,  
Edinboro, PA 16412-0754  
sales@beaconlubricants.com

toll free: (877) 734-7334  
phone: (814) 734-7535  
fax: (814) 734-3460

safety data sheet

Single Exposure: No end point data for material	Not expected to cause organ damage from a single exposure
Repeated Exposure: No end point data for material	Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components.

## TOXICITY FOR SUBSTANCES

### OTHER INFORMATION

**For the product itself:** Repeated and/or prolonged exposure may cause irritation to the skin, eyes or respiratory tract. Oil Mist (highly refined oils): Animals exposed to high concentrations of mist developed oil retention, inflammation, and oil granulomas in the respiratory tract. Oils exposed to high temperatures, cracking conditions, or mixing with tramp / used oils may introduce polycyclic aromatic compounds or microbial contaminants that could result in cancer or severe respiratory hazards.

### Contains:

base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitizing in test animals.

**The following ingredients are cited on the lists below: None.**

--REGULATORY LISTS SEARCHED--

1 = NTP CARC 3 = IARC 1 5 = IARC 2B

2 = NTP SUS 4 = IARC 2A 6 = OSHA CARC

## SECTION 12

## ECOLOGICAL INFORMATION

The information given is based on data available for the material, the components of the material, and similar materials.

### ECOTOXICITY

Material — Not expected to be harmful to aquatic organisms.

### MOBILITY



P.O. Box 754,  
Edinboro, PA 16412-0754  
sales@beaconlubricants.com

toll free: (877) 734-7334  
phone: (814) 734-7535  
fax: (814) 734-3460

safety data sheet

Components — Expected to remain in water or migrate through soil.

## **PERSISTENCE AND DEGRADABILITY**

### **Biodegradation:**

Base Oil Components— Expected to be inherently biodegradable

## **BIOACCUMULATION POTENTIAL**

Components — Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bio concentration or limit bioavailability

## **OTHER ECOLOGICAL INFORMATION**

**VOC:** 4.2 G/L [ASTM E1868-10]

## **SECTION 13**

## **DISPOSAL CONSIDERATIONS**

Disposal recommendations based on material as supplied. Disposal must be in accordance current applicable laws and regulations, and material characteristics at time of disposal.

### **DISPOSAL RECOMMENDATIONS**

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

### **REGULATORY DISPOSAL INFORMATION**

RCRA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

**Empty Container Warning:** Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.



P.O. Box 754,  
Edinboro, PA 16412-0754  
sales@beaconlubricants.com

toll free: (877) 734-7334  
phone: (814) 734-7535  
fax: (814) 734-3460

safety data sheet

## SECTION 14

## TRANSPORT INFORMATION

**LAND (DOT):** Not Regulated for Land Transport

**LAND (TDG):** Not Regulated for Land Transport

Footnote: Regulated under TDG as UN 308, Environmentally Hazardous Substance, liquid, Class 9, Marine Pollutant, only when transported by ship.

**SEA (IMDG):** Not Regulated for Sea Transport according to IMDG-Code

Marine Pollutant: No

**AIR (IATA):** Not Regulated for Air Transport

## SECTION 15

## REGULATORY INFORMATION

**OSHA HAZARD COMMUNICATION STANDARD:** This material is considered hazardous in accordance with OSHA HazCom 2012, 29, CFR 1910. 1200.

**Complies with the following national/regional chemical inventory requirements:** DSL, IECSC, KECI, PICCS, TSCA

**EPCRA SECTION 302:** This material contains no extremely hazards substances.

**SARA (311/312) REPORTABLE HAZARD CATEGORIES:** None

**SARA (313) TOXIC RELEASE INVENTORY:** This material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

**The following ingredients are cited on the lists below:**

N/A

--REGULATORY LISTS SEARCHED--

1 = ACGIH ALL	6 = TSCA 5a2	11 = CA P65 REPRO	16 = MN RTK
2 = ACGIH A1	7 = TSCA 5e	12 = CA RTK	17 = NJ RTK
3 = ACGIH A2	8 = TSCA 6	13 = IL RTK	18 = PA RTK
4 = OSHA Z	9 = TSCA 12b	14 = LA RTK	19 = RI RTK
5 = TSCA 4	10 = CA P6 CARC	15 = MI 293	



P.O. Box 754,  
Edinboro, PA 16412-0754  
sales@beaconlubricants.com

toll free: (877) 734-7334  
phone: (814) 734-7535  
fax: (814) 734-3460

safety data sheet

Code Key: CARC=Carcinogen; REPRO=Reproductive

## SECTION 16

## OTHER INFORMATION

N/D = Not determined, N/A = Not applicable

### **KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):**

#### **THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**

Updates made in accordance with implementations of GHS requirements.

The information and recommendations contained herein are, to the best of Beacon Lubricants knowledge and belief, accurate and reliable as of the date issued. You can contact Beacon Lubricants to insure that this document is the most current available from Beacon Lubricants. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for intended use. If the buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted.