



P.O. Box 754,
Edinboro, PA 16412-0754

sales@beaconlubricants.com

toll free: (877) 734-7334
phone: (814) 734-7535
fax: (814) 734-3460

technical data sheet

Anti-Rust 156

Product Application:

Beacon Anti-Rust 156 is premium quality transparent lightly colored water displacing non-staining rust and corrosion preventative. It is formulated using the latest approved technology in light-bodied oils and hydro treated solvents blended with polar corrosion inhibitors, water displacing and fingerprint neutralizing agents.

Anti-Rust 156 is well suited for the thin film protection of parts between machining where water-based coolants has been used. It has a light viscosity which assures adequate coverage of metal surfaces while allowing excess fluid to drain rapidly thus allowing for a smooth efficient application.

Beacon Anti-Rust 156 is an excellent light bodied nonconductive rust and corrosion preventative for finished parts in dry storage or for adequately covered or bagged transport.

Meets or Exceeds that following Specifications:

Military Specifications PRF16173E
Military Specifications MIL-C-15074E

Theoretical Coverage:

2,500 sq. ft. /gallon

Typical Characteristics:

Specific Gravity @ 60 °F	.82
Flash Point, COC, °F	160
Pour Point, °F	-20
Appearance	Light Amber
Film Thickness	.15 mil
Cure Time- Approximately	2 hours

Corrosion Test Results:

ASTM B-117 5 % salt spray (hours)	116
ASTM D-1748 100 % relative humidity (hours)	1825
Corrosion Test Mil-C-23411	pass
Corrosion Test Mil-C-81309	pass
Water displacement	pass
Stain test (Mil-C-22235A)	pass

Visit us at – www.beaconlubricants.com