






# 1. PATTERN AND REPEAT

# 18"

## 2. LAYOUT SUGGESTIONS



# SPECIFICATIONS

WOOD TILE CONSTRUCTION:

Engineered wood.

4mm wear layer over 9 ply substrate.

THICKNESS:

5/8 inches. REPEAT:

**BOX QUANTITY:** 

26.25 SF per box. 30 tiles total per box.

COVERAGE PER TILE:

.875 SF

INSTALLATION:

Glue down. (See installation guidelines) Wood tiles are NOT provided on a mesh or panel backing.

**USAGE:** 

Warranted for Commercial or Residential floors,

walls & ceilings.

Not suitable for areas exposed to running water:

inside showers, etc.

Not suitable for outdoor applications.

LEADTIME:

6-8 weeks for production.

Expedited options available upon request for an upcharge.

Varies by pattern & wood species. Multiple stain selections do not affect pricing. FIRE RATING:

Class C. (Class B available upon request)

STAINING SYSTEM:

Rubio Monocoat hard oil finish - no VOC.

Available unfinished.

LEED CREDITS:

2009 NC/CI MR Credit 5 - Regional Materials 2009 NC/Cl IEQ Credit 4.1-4.4 - Low Emitting Finish

\*\*\*This product may contribute to the achievement of LEED credits, although JBC makes no guarantees of representation of such

CAD PATTERNS AVAILABLE UPON REQUEST.

Contact your local JBC representative.

### 3. SPECIES



Plain White Oak Walnut



Quarter White

### 4. STAINS





Polished Amber Dolphin



Smokey Quartz Black Onyx Grey Moonstone Pickled Pearl





















AVAILABLE ON WALNUT SPECIES:



Dolphin



Smokey Quartz











