

20' HIGH CUBE - DOUBLE DOOR OFFSHORE CONTAINER

20' x 8' x 9'6" High Cube Height - Corrugated Panel
 Double Cargo Doors on BOTH ends
 Hot Dip Galvanized or Painted Finish



CERTIFICATIONS

DNV 2.7-1 (DNV-ST-E271) Standard for Offshore Containers
 ISO 10855 International Standard for Offshore Containers and associated lifting sets
 In support of IMO MSC Circ 860
 CSC Convention for Safe Containers
 API / Shell OPS0055 by request
 Classification Society : Lloyd's Register (LR) or Det Norske Veritas (DNV)

DIMENSIONS (+/- 1/4" 6mm)

| | EXTERNAL | INTERNAL |
|-------------------------|---------------|--|
| Length | 6058 mm 20' | 5830 mm 19'- 1 33/64" |
| Width | 2438 mm 8' | 2218 mm 7'- 7 9/16" |
| Height | 2896 mm 9'-6" | 2520 mm 8'- 3 13/64" |
| Door Opening Width | | 2218 mm 7'-3 5/16" |
| Door Opening Height | | 2481 mm 8'-1 43/64" |
| Internal Cubic Capacity | | 32.6 M ³ 1151 FT ³ |



RATINGS (+/- 3%)

For Offshore / Sling Movement

| | | |
|------------------|-----------|------------|
| Max Gross Weight | 19,030 kg | 41,950 lbs |
| Max Payload | 15,000 kg | 33,070 lbs |
| Tare Weight | 4,030 kg | 8,880 lbs |

For Standard Cargo / Fork Lift / Top Lift Movement

| | | |
|------------------|-----------|------------|
| Max Gross Weight | 30,480 kg | 67,200 lbs |
| Max Payload | 26,450 kg | 58,320 lbs |
| Tare Weight | 4,030 kg | 8,880 lbs |

INCLUDES

- DNV Certified Wire Rope Lifting Sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

