

6' PALLET OFFSHORE CONTAINER

6' x 6' x 6'

Hot Dipped Galvanized



CERTIFICATIONS

DNV 2.7-1 (DNVGL-ST-E271) Standard for Offshore Containers

ISO 10855 International Standard for Offshore Containers and associated lifting sets

In support of IMO MSC Circ 860

CSC Convention for Safe Containers

API / Shell OPS0055 by request

Classification Society : Lloyd's Register or DNV GL

DIMENSIONS (+/- 4/16")

	EXTERNAL		INTERNAL	
Length	1800 mm	5'-11"	1605 mm	5'-3 3/16"
Width	1770 mm	5'-10"	1610 mm	5'-3 6/16"
Height	1830 mm	6'	1463 mm	4'-7 7/16"

Door Opening Width	1610 mm	5'-3 6/16"
Door Opening Height	1408 mm	4'-7 7/16"
Internal Cubic Capacity	3.77 M ³	133 FT ³


RATINGS (+/- 3%)

For Offshore / Sling Movement

Max Gross Weight	5,200 kg	11,465 lbs
Max Payload	4,000 kg	8,820 lbs
Tare Weight	1,200 kg	2,645 lbs

For Standard Cargo / Lift Movement

Max Gross Weight	5,200 kg	11,465 lbs
Max Payload	4,000 kg	8,820 lbs
Tare Weight	1,200 kg	2,645 lbs



INCLUDES

- DNV Certified Wire Rope lifting sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

