

20' TARPED OPEN TOP OFFSHORE CONTAINER

20' x 8' x 8'6" Standard Height - Corrugated Panel
 Double Cargo Doors on one end & Open Top
 Hot Dip Galvanized or Painted Finish
 Roof Bows Included



CERTIFICATIONS

DNV 2.7-1 (DNVGL-ST-E271) Standard for Offshore Containers
 ISO 10855 International Standard for Offshore Containers and associated lifting sets
 In support of IMO MSC Circ 860
 CSC Convention for Safe Containers
 API / Shell OPS0055 by request
 Classification Society : Lloyd's Register (LR) or Det Norske Veritas (DNV)

DIMENSIONS (+/- 1/4")

	EXTERNAL	INTERNAL
Length	6058 mm 20'	5836 mm 19' - 1 3/4"
Width	2438 mm 8'	2218 mm 7' - 7 9/16"
Height	2591 mm 8'-6"	2284 mm 7' - 5 29/32"
Door Opening Width		2218 mm 7' - 3 5/16"
Door Opening Height		2149 mm 7' - 0 19/32"
Internal Cubic Capacity		29.6 M ³ 1045 FT ³
Top Opening L x W		5784 x 2196 mm **

RATINGS (+/- 3%)

For Offshore / Sling Movement

Max Gross Weight	19,700 kg	43,430 lbs
Max Payload	16,000 kg	35,270 lbs
Tare Weight	3,700 kg	8,160 lbs

For Standard Cargo / Fork Lift / Top Lift Movement

Max Gross Weight	30,480 kg	67,200 lbs
Max Payload	26,780 kg	59,040 lbs
Tare Weight	3,700 kg	8,160 lbs



INCLUDES

- DNV Certified Wire Rope Lifting Sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

