



## Safety Data Sheet: Signal Tumbler H<sub>2</sub>O GP

Revision Date: January 2<sup>nd</sup> 2024

### SECTION 1

### PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT

**Product Name:** Signal Tumbler H<sub>2</sub>O GP

**Product Description:** Base Oil and Additives

**Intended Use:** Industrial machining tumblers

#### COMPANY IDENTIFICATION

**Supplier:** Beacon Lubricants  
P.O Box 754  
Edinboro, PA 16412

**Emergency Telephone:** 1-877-734-7334 – Beacon Lubricants, Inc.

**Emergency Telephone:** 1-800-424-9300 (24 hours) – Chemtrec

Visit us at [www.beaconlubricants.com](http://www.beaconlubricants.com)

### SECTION 2

### HAZARDS IDENTIFICATION

This material is hazardous according to regulatory guidelines (see (M)SDS Section 15).

CLASSIFICATION:

Aspiration toxicant: Category 1.

LABEL:

Pictogram:



Signal Word: Warning

Hazard Statements:

H317: May cause allergic skin reaction.



**Precautionary Statements:**

P261: Avoid breathing mist / vapors. P272: Contaminated work clothing should not be allowed out of the workplace. P273: Avoid release to the environment. P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P333 + P313: If skin irritation or rash occurs: Get medical advice/attention. P362 +P364: Take off contaminated clothing and wash it before reuse. P501: Dispose of contents and container in accordance with local regulations.

**Contains:** OXAZOLIDINE

**Other hazard information:**

**HAZARD NOT OTHERWISE CLASSIFIED (HNOC):** None as defined under 20 CFR 1900.1200.

**PHYSICAL / CHEMICAL HAZARDS**

No significant hazards.

**HEALTH HAZARDS**

High-pressure injection under skin may cause serious damage. This product may be used in certain applications where misting can occur. Excessive exposure to liquids and mists may cause skin and eye irritation. In addition, excessive exposure to mists may cause respiratory irritation and damage and aggravate pre-existing emphysema or asthma. Repeated exposure may cause skin dryness or cracking. Mists may be irritating to eyes, nose, throat, and lungs. Excessive exposure may result in eye, skin, or respiratory irritation.

**ENVIRONMENTAL HAZARDS**

Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

<b>NFPA HAZARD ID:</b> Health: 2	Flammability: 1	Reactivity: 0
<b>HMIS HAZARD ID:</b> Health: 2	Flammability: 1	Reactivity: 0

**Note:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks, which may vary from person to person.



**SECTION 3 COMPOSITION / INFORMATION INGREDIENTS**

This material is defined as a mixture.

**Hazardous Substance(s) or Complex Substance(s) required for disclosure.**

Name	CAS #	Concentration*	GHS Hazard Codes
1H, 3H, 5H – OXAZOLO, &A-ETHYLDIHYDRO-	7747-35-5	0.1 - < 1 %	H315, H318, H317
ALCOHOLS, C12-15 ETHOXYLATED	68131-39-5	0.1 - < 1 %	H302, H318, H400, (M factor)
FATTY ACIDS, TALL-OIL COMPOUNDS WITH DIISOPROPANOLAMINE	68953-28-6	1 - < 5 %	H315, H319 (2A)
SEVERLY HYDROTREATED HEAVY PARAFFINIC DISTILLATE	64742-54-7	40 - < 50 %	H304
SODIUM PETROLEUM SULFONATE	68608-26-4	1 - < 5 %	H318
SOLVENT DEWAXED HEAVY PARAFFINIC DISTILLATE	64742-65-0	40 - < 50 %	H304
TALL OIL ACIDS AND NAPHTHETNIC ACIDS, POTASSIUM SALTS	confidential	1 - < 5 %	H319 (2A)

All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

As per paragraph (i) of 29 CFR 1910. 1200, formulation is considered a trade secret and specific chemical identity and exact percentage (concentration) of composition may have been withheld. Specific chemical identity and exact percentage composition will be provided to health professionals, employees, or designated representatives in accordance with applicable provisions of paragraph (i).

**SECTION 4 FIRST AID MEASURES**

**INHALATION**



Remove from further exposure. For those providing assistance, avoid exposure to yourself and others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

### SKIN CONTACT

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

### EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

### INGESTION

First aid is normally not required. Seek medical attention if discomfort occurs.

## SECTION 5

## FIRE FIGHTING MEASURES

### EXTINGUISHING MEDIA

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Inappropriate Extinguishing Media:** Straight Steams of Water

### FIRE FIGHTING

**Fire Fighting Instructions:** Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire-exposed surfaces and to protect personnel.

**Hazardous Combustion Products:** Sulfur oxides, Aldehydes, Smoke, Fume, Oxides of carbon, incomplete combustion products.

### FLAMMABILITY PROPERTIES

Flash Point [Method]: >179°C (354°F) [ASTM D-92]



Flammable Limits (Approximate volume % in air): LEL: 0.9 UEL: 7.0

Auto ignition Temperature: N/D

## SECTION 6

## ACCIDENTAL RELEASE MEASURES

### NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting release of this material to the environment, which exceed the applicable reportable quantity or oil spills, which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at 800-424-8802.

### PROTECTIVE MEASURES

Avoid contact with spilled material. See Section 5 for firefighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

**For emergency responders:** Respiratory protection: respiratory protection will be necessary online in special cases, e.g., formation of mists. Half-face or full-face respirators with filter(s) for dust/organic vapor or Self-Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Work gloves that are resistant to hydrocarbons are recommended. Gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large Spills: full body suit of chemical resistant, antistatic material is recommended.

### SPILL MANAGEMENT

**Land Spill:** Stop leak if you can do it without risk. Recover by pumping or with suitable absorbent.

**Water Spill:** Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by



skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

## ENVIRONMENTAL PRECAUTIONS

**Large Spills:** Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

## SECTION 7

## HANDLING AND STORAGE

### HANDLING

Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges, which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or ground procedures. However, bonding and ground may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional reference includes American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics- Code of practice for the avoidance of hazards due to static electricity).

**Static Accumulator:** This material is a static accumulator.

### Storage:

The container choice, for example storage vessel, may affect static accumulation and dissipation. Do not store in open or unlabeled containers. Keep away from incompatible materials.



**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

Exposure limits/standards for materials that can be formed when handling this product: When mists/aerosols can occur, the following are recommended: 5 mg/m<sup>3</sup> – ACGIH TLV (inhalable fraction), 5mg/m<sup>3</sup> – OSHA PEL.

Substance Name	Form	Limit / Standard		NOTE	Source
SEVERLY HYDROTREATED HEAVY PARAFFINIC DISTILLATE	Inhalable fraction.	TWA	5 mg/m <sup>3</sup>	N/A	ACGIH
SEVERLY HYDROTREATED HEAVY PARAFFINIC DISTILLATE	Mist.	TWA	5 mg/m <sup>3</sup>	N/A	ACGIH
SOLVENT DEWAXED HEAVY PARAFFINIC DISTILLATE	Mist.	TWA	5 mg/m <sup>3</sup>	N/A	OSHA Z1
SOLVENT DEWAXED HEAVY PARAFFINIC DISTILLATE		TWA	2000 mg/m <sup>3</sup>	N/A	OSHA Z1
SOLVENT DEWAXED HEAVY PARAFFINIC DISTILLATE	Mist.	TWA	5 mg/m <sup>3</sup>	N/A	ACGIH

Note: Limits/standards shown for guidance only. Follow applicable regulations.

No biological limits allocated.

**ENGINEERING CONTROLS**

The level of protection and types of controls necessary will vary depending upon potential exposure conditions.

**Control measures to consider:**

No special requirements under ordinary conditions of use and with adequate ventilation.

**PERSONAL PROTECTION**

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.





**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level, which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: No special requirements under ordinary conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filters capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove stability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for you use conditions. Inspect and replace worn or damaged gloves. The types of glove to be considered for this material include:

No protection is ordinarily required under normal conditions of use.

**Eye Protection:** If contact is likely, safety glasses with side shields are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

## **ENVIRONMENTALS CONTROLS**

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.





## SECTION 9

## PHYSICAL AND CHEMICAL PROPERTIES

**Note:** Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

### GENERAL INFORMATION

**Physical State:** Liquid

**Color:** Yellow

**Odor:** Characteristic

**Odor Threshold:** N/D

### IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

**Relative Density (at 15 °C):** .089

**Flammability (Solid, Gas):** N/A

**Flash Point [Method]** > 179°C (354°F) [ASTM D-92]

**Flammable Limits (Approximate volume % in air):** LEL: 0.9 UEL: 7.0

**Auto ignition Temperature:** N/D

**Boiling Point / Range:** 270 °C (518°F) – 500 °C (932°F) [Estimated]

**Decomposition Temperature:** N/D

**Vapor Density (Air =1):** > 232°C (450°F)

**Vapor Pressure:** 2 at 101 kPa [Estimated]

**Evaporation Rate (n-butyl acetate = 1):** < 0.1

**pH:** N/A

**Log Pow (n-Octanol/Water Partition Coefficient):** N/D

**Solubility in Water:** Emulsifies

**Viscosity:** 35 cSt (35 mm<sup>2</sup>/sec) @ 40 °C

### OTHER INFORMATION

**Freezing Point:** N/D

**Melting Point:** N/A

**Pour Point:** -6°C (21°F)

**DMSO Extract (mineral oil only), IP-346:** < 3 % wt

## SECTION 10

## STABILITY AND REACTIVITY

**REACTIVITY:** See sub-sections bellows.

**STABILITY:** Material is stable under normal conditions

**CONDITIONS TO AVOID:** Excessive heat. High-energy sources of ignition

**MATERIALS TO AVOID:** Strong oxidizers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose to ambient temperatures.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.

**SECTION 11**
**TOXICOLOGICAL INFORMATION**
**INFORMATION ON TOXICOLOGICAL EFFECTS**

<b>Hazard Class</b>	<b>Conclusion / Remarks</b>
<b>Inhalation</b>	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data for material	Negligible hazard at ambient/normal handling temperatures.
<b>Ingestion</b>	
Acute Toxicity: No end point data for material	Minimally Toxic. Based on assessment of the components.
<b>Skin</b>	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin Corrosion/Irritation: No end point data for material.	Negligible irritation to skin at ambient temperatures. Based on assessment of the components.
<b>Eye</b>	
Serious Eye Damage/Irritation: No end point data for material.	May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.
<b>Sensitization</b>	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: No end point data for material	Not expected to be a skin sensitizer. Based on assessment of the components.
Aspiration: Data available	Not expected to be an aspiration hazard. Based on physic-chemical properties of the material.



P.O. Box 754,  
Edinboro, PA 16412-0754

sales@beaconlubricants.com

toll free: (877) 734-7334

phone: (814) 734-7535

fax: (814) 734-3460

safety data sheet

Germ Cell Mutagenicity: No end point data for material	Not expected to be a germ cell mutagen. Based on assessment of the components.
Carcinogenicity: No end point data for material	Not expected to cause cancer. Based on assessment of the components.
Reproductive Toxicity: No end point data for material	Not expected to be a reproductive toxicant. Based on assessment of the components.
Lactation: No end point data for material.	Not expected to cause harm to breast-fed children
<b>Specific Target Organ Toxicity (STOT)</b>	
Single Exposure: No end point data for material	Not expected to cause organ damage from a single exposure.
Repeated Exposure: No end point data for material.	Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components.

## OTHER INFORMATION

### For the product itself:

Vapor concentrations above are recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anesthetic and may have other central nervous system effects. Prolonged and/or repeated skin contact with low viscosity materials may defat the skin resulting in possible irritation and dermatitis. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema. Middle distillates: Carcinogenic in animal tests. Lifetime skin painting tests produced tumors, but the mechanism is due to repeated cycles of skin damage and restorative hyperplasia. This mechanism is considered unlikely in humans where such prolonged skin irritation would not be tolerated. Did not cause mutations in Vitro. Inhalation of vapors did not result in reproductive or developmental effects in laboratory animals. Inhalation of high concentrations in animals resulted in respiratory tract irritation, lung changes and some reduction in lung function. Non-sensitizing in test animals. Oil Mist (highly refined oils): Animals exposed to high temperatures, cracking conditions, or mixing with tramp / used oils may introduce polycyclic aromatic compounds or microbial contaminants that could result in cancer or severe respiratory hazards.



P.O. Box 754,  
Edinboro, PA 16412-0754

sales@beaconlubricants.com

toll free: (877) 734-7334

phone: (814) 734-7535

fax: (814) 734-3460

safety data sheet

The following ingredients are cited on the lists below: None.

--REGULATORY LISTS SEARCHED--

1= NTP CARC

3. IARC 1

5 = IARC 2B

2= NTP SUS

4. IARC 2A

6. OSHA CARC

## SECTION 12

## ECOLOGICAL INFORMATION

The information given is based on data available for the material, the components of the material, and similar materials.

### ECOTOXICITY

Material – Expected to be harmful to aquatic organisms.

### PERSISTENCE AND DEGRADABILITY

#### Biodegradation:

**Base oil component** – Expected to be inherently biodegradable

### OTHER ECOLOGICAL INFORMATION

**VOC:** 10.2 G/L [ASTM E1868-10]

## SECTION 13

## DISPOAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations and material characteristics at time of disposal.

### DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

### REGULATORY DISPOSAL INFORMATION

**RCRA Information:** The unused product, in our opinion is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials, which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

**Empty Container Warning- Empty Container Warning (where applicable):** Empty containers may contain residue and can be dangerous. Do not attempt to refill



or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITIONS. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

**SECTION 14** **TRANSPORT INFORMATION**

**LAND (DOT):** Not regulated for Land Transport

**LAND (TDG):** Not regulated for Land Transport

**SEA (IMDG):** Not regulated for Sea Transport according to IMDG-Code  
**Marine Pollutant:** No

**AIR (IATA):** Not regulated for Air Transport

**SECTION 15** **REGULATORY INFORMATION**

**OSHA HAZARD COMMUNICATION STANDARD:** This material is not considered hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200

Listed or exempt from listing/notification on the following chemical inventories:  
DSL, IECSC, TSCA

**EPCRA SECTION 302:** This material contains no extremely hazardous substances.

**SARA (311/312) REPORTABLE HAZARD CATEGORIES:** Immediate Health.

**SARA (313) TOXIC RELEASE INVENTORY:** This material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

The following ingredients are cited on the lists below: None

REGULATORY LISTS SEARCHED

- |              |             |                  |            |
|--------------|-------------|------------------|------------|
| 1= ACGIH ALL | 6= TSCA 5a2 | 11= CA p65 REPRO | 16= MN RTK |
| 2= ACGIH A1  | 7= TSCA 5e  | 12= CA RTK       | 17= NJ RTK |
| 3= ACGIH A2  | 8= TSCA 6   | 13= IL RTK       | 18= PA RTK |



**beacon  
lubricants**<sub>INC</sub>

P.O. Box 754,  
Edinboro, PA 16412-0754  
sales@beaconlubricants.com

toll free: (877) 734-7334  
phone: (814) 734-7535  
fax: (814) 734-3460

safety data sheet

4= OSHA Z  
5= TSCA 4

9= TSCA 12b  
10= CA P65 CARC

14= LA RTK  
15= MI 293

19= RI RTK

Code Key: CARC+Carcinogen; REPRO=Reproductive

## SECTION 16

## OTHER INFORMATION

N/D= Not determined, N/A = Not applicable

KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

H302: Harmful if swallowed; Acute Tox Oral, Cat 4

H304: May be fatal if swallowed and enters airways; Aspiration, Cat 1

H315: Causes skin irritation; Skin Corr/Irritation, Cat 2

H317: May cause allergic skin reaction; Skin Sensitization, Cat 1

H318: Causes serious eye irritation; Serious Eye Damage/Irr, Cat 2A

H319(2A): Causes serious eye irritation; Serious Eye Damage/Irr, Cat 2A

H400: Very toxic to aquatic life; Acute Env Tox, Cat 1

### **THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**

Updates made in accordance with implementation of GHS requirements.

The information and recommendations contained herein are, to the best of Beacon Lubricant's knowledge and belief, accurate and reliable as of the date issued. You can contact Beacon Lubricant's to ensure that this document is the most current available for Beacon Lubricant's. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use.