

Anti-Rust 159

Product Application:

Beacon Anti-Rust 159 is premium quality transparent lightly colored water displacing nonstaining rust and corrosion preventative. It is formulated using the latest approved technology in medium-bodied oils and hydro treated solvents blended with polar corrosion inhibitors, water displacing and fingerprint neutralizing agents.

Anti-Rust 159 is well suited for the thin film protection of parts between machining where water-based coolants have been used. It has a medium viscosity which assures robust coverage of metal surfaces while allowing excess fluid to drain rapidly thus allowing for a smooth efficient application with a light oil film protective layer.

Beacon Anti-Rust 159 is an excellent medium bodied rust and corrosion preventative for finished parts in dry storage or for adequately covered or bagged transport.

Meets or Exceeds that following Specifications:

Military Specifications PRF16173E - Grades 2, 3 Military Specifications MIL-C-15074E Military Specifications MIL-PFR-3150

Theoretical Coverage:

3,000 sq. ft. /gallon

Typical Characteristics:		
Specific Gravity @ 60 °F	.80	
Flash Point, COC, °F	210	
Pour Point, °F	-20	
Appearance	Light Amber	
Film Thickness	.15	
Cure Time- Approximately	2 hours	
Corrosion Test Results:		

ASTM B-117 5 % salt spray (hours)	134
ASTM D-1748 100 % relative humidity (hours)	2300

Visit us at - www.beaconlubricants.com