

6' FLAT PANEL OFFSHORE CONTAINER

6' x 6' x 8'

Optional Cabinetry

Hot Dipped Galvanized

CERTIFICATIONS

DNV 2.7-1 (DNVGL-ST-E271) Standard for Offshore Containers

ISO 10855 International Standard for Offshore Containers and associated lifting sets

In support of IMO MSC Circ 860

CSC Convention for Safe Containers

API / Shell OPS0055 by request

Classification Society : Lloyd's Register or DNV GL



DIMENSIONS (+/- 4/16")

	EXTERNAL		INTERNAL	
Length	1800 mm	5'-11"	1619 mm	5'-3 3/4"
Width	1770 mm	5'-10"	1610 mm	5'-3 3/8"
Height	2435 mm	7'-12"	2077 mm	6'-9 3/4"

Door Opening Width	1610 mm	5'-3 3/8"
Door Opening Height	2011 mm	6'-7 3/16"
Internal Cubic Capacity	5.41 M ³	191 FT ³

RATINGS (+/- 3%)

For Offshore / Sling Movement

Max Gross Weight	5,400 kg	11,905 lbs
Max Payload	4,000 kg	8,820 lbs
Tare Weight	1,400 kg	3,058 lbs

For Standard Cargo / Lift Movement

Max Gross Weight	5,400 kg	11,905 lbs
Max Payload	4,000 kg	8,820 lbs
Tare Weight	1,400 kg	3,058 lbs



INCLUDES

- DNV Certified Wire Rope lifting sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

