

variations

ENGINEERED WOOD FOR FLOORS, WALLS & CEILINGS



JAMIE BECKWITH®
COLLECTION

JEFF ANDREWS


VARIATIONS

FOR

JAMIE BECKWITH®
COLLECTION

1. PATTERNS

PATTERNS SUITABLE FOR FLOORS, WALLS & CEILINGS:



Angles




Lines




Knotted

PATTERNS SUITABLE FOR WALLS & CEILINGS ONLY:



Hour Glass



Steps



Forms




Arches

2. STAINS


HOURLASS, STEPS, ARCHES &
LINES
ON PLAIN WHITE OAK




Driftwood



Natural



Light




Medium




Palette #1
on Walnut




Palette #2
on White Oak



Bark



Slate



Dark



Palette #3
on White Oak

SPECIFICATIONS

WOOD TILE CONSTRUCTION:

4mm wear layer over 9 ply substrate.
5/8" Thickness.

INSTALLATION:

Glue down. (See installation guidelines)

FIRE RATING:

Class C. (Class B available upon request)

BOX QUANTITY:

Varies by pattern

USAGE:

Warranted for Commercial or Residential floors, walls & ceilings. (Application varies by pattern).

Not suitable for areas exposed to running water: inside showers, etc.

Not suitable for outdoor applications.

LEADTIME:

6-8 weeks for production.

Expedited options available upon request.

STAINING SYSTEM:

Rubio Monocoat hard oil finish - no VOC.
Available unfinished.

LEED CREDITS:

2009 NC/CI MR Credit 5 - Regional Materials

2009 NC/CI IEQ Credit 4.1-4.4 - Low Emitting Finish

***This product may contribute to the achievement of LEED credits, although JBC makes no guarantees of representation of such.