

Bonestock Compacts Rules:

Rule questions call Greg at 217-714-9997. No calls after 7pm.

- All cars must be completely stripped.
- Gas tank and battery should be secured inside the car.
- **Gas tank-** protector must be 7" away from all sheet metal.
- **Tires-** stock, mud, or donut.
- **Hood-** #9 wire 4 spots. Can go down to the bumper, front and rear. No sheet creasing or shaping.
- **Trunk-** #9 wire 4 spots. Can 90 trunk. No sheet creasing or shaping.
- **Doors-** #9 wire all doors closed or you can weld doors shut with (2) 12"x1"x 1/8" strap per side of the car.
- **Cage-** 4-point cage with halo. You may have a down bar on the driver and passenger sides. Door bars cannot exceed 60". Must be 4" away from the firewall.
- **Bumpers** – Automobile or aftermarket bumper or a 4x4 square tube can be used. Bumpers can be 8" tall max. Bumper shocks can be 2"x2" square tube 8" long.
- **Fresh-** (2) 4x4 plates 1/8" thick
- **Pre Rans-** (5) 6x6 plates 1/8" thick.
- The only aftermarket parts allowed are-
 - Battery box
 - Shifter
 - Gas tank
 - Trans cooler
 - Headers
 - Wiring harness