

# 4' OFFSHORE CARGO BASKET

## 4' x 4' x 3'1"

Optional Aluminum Lid

D rings Top and Bottom Rails

Hot Dip Galvanized or Painted Finish



## CERTIFICATIONS

DNV 2.7-1 (DNVGL-ST-E271) Standard for Offshore Containers

ISO 10855 International Standard for Offshore Containers and associated lifting sets

In support of IMO MSC Circ 860

API / Shell OPS0055 by request

Classification Society : Lloyd's Register (LR) or Det Norske Veritas (DNV)

## DIMENSIONS (+/- 1/4")

	EXTERNAL	INTERNAL
Length	1220 mm 4'	1048 mm 3'-5 1/4"
Width	1220 mm 4'	1048 mm 3'-5 1/4"
Height	955 mm 3'-1"	728 mm 2'-4 21/32"
Top Opening LxW		1048 mm x 1048 mm*
Lid Opening LxW		975 mm x 780 mm
Internal Cubic Capacity		.8 Cu M 28 Cu FT

\*does not include pad eye dimensions

## RATINGS (+/- 3%)

For Offshore / Sling Movement

Max Gross Weight	2,520 kg	5,560 lbs
Max Payload	1,950 kg	4,300 lbs
Tare Weight	570 kg	1,260 lbs



## INCLUDES

- DNV Certified Wire Rope Lifting Sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

