

20' OFFSHORE LIFTING FRAME

20' x 8' x 8'6"

Hot Dip Galvanized or Painted Finish

CERTIFICATIONS

DNV 2.7-1 (DNV-ST-E271) Standard for Offshore Containers

ISO 10855 International Standard for Offshore Containers and associated lifting sets

CSC Convention for Safe Containers

In support of **IMO MSC Circ 860**

ISO 1161 Corner Fittings

API / Shell OPS0055 by request

Classification Society : **Lloyd's Register** or **Det Norske Veritas (DNV)**



DIMENSIONS (+/- 1/4")

| | EXTERNAL | | INTERNAL | |
|--------|----------|-------------|----------|--------------|
| Length | 6058 mm | 19'-10 1/2" | 6038 mm | 19'-9 11/16" |
| Width | 2438 mm | 8' | 2178 mm | 7'-1 3/4" |
| Height | 2591 mm | 8' 6 " | 2266 mm | 7'-5 3/16" |



RATINGS (+/- 3%)

For Offshore / Sling Movement

| | | |
|----------------------|-----------|------------|
| Max Gross Offshore | 25,000 kg | 55,115 lbs |
| Max Gross ISO | 30,480 kg | 67,196 lbs |
| Payload Offshore | 21,000 kg | 46,297 lbs |
| Payload ISO | 26,480 kg | 58,378 lbs |
| Tare Weight (+/- 2%) | 4,000 kg | 8,818 lbs |

INCLUDES

- DNV Certified Wire Rope lifting sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

