

10' RIGGING LOFT OFFSHORE CONTAINER

10' x 8' x 8'6" Standard Height
Double Cargo Doors on one end
Hot Dip Galvanized Finish



CERTIFICATIONS

DNV 2.7-1 (DNV-ST-E271) Standard for Offshore Containers
ISO 10855 International Standard for Offshore Containers and associated lifting sets
In support of IMO MSC Circ 860
CSC Convention for Safe Containers
API / Shell OPS0055 by request
Classification Society : Lloyd's Register (LR) or Det Norske Veritas (DNV)

DIMENSIONS (+/- 1/4")

	EXTERNAL	INTERNAL
Length	2991 mm 9' - 9 3/4"	2802 mm 9' - 2 5/16"
Width	2438 mm 8'	2288 mm 7' - 6 5/64"
Height	2591 mm 8' - 6"	2238 mm 7' - 4 7/64"
Door Opening Width		2258 mm 7' - 4 57/64"
Door Opening Height		2253 mm 7' - 4 11/16"
Internal Cubic Capacity		14.3 M ³ 505 FT ³



RATINGS (+/- 3%)

For Offshore / Sling Movement

Max Gross Weight	10,000 kg	22,050 lbs
Max Payload	7,800 kg	17,200 lbs
Tare Weight	2,200 kg	4,850 lbs

For Standard Cargo / Fork Lift Movement

Max Gross Weight	10,000 kg	22,050 lbs
Max Payload	7,800 kg	17,200 lbs
Tare Weight	2,200 kg	4,850 lbs

INCLUDES

- DNV Certified Wire Rope Lifting Sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

