



**beacon
lubricants** INC

P.O. Box 754,
Edinboro, PA 16412-0754
sales@beaconlubricants.com

toll free: (877) 734-7334
phone: (814) 734-7535
fax: (814) 734-3460

safety data sheet

Safety Data Sheet: Signal Cut 211C

Revision Date: January 2nd 2024

SECTION 1

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name: Signal Cut 211C

Intended Use: Machining Coolant

COMPANY IDENTIFICATION

Supplier: Beacon Lubricants
P.O Box 754
Edinboro, PA 16412

Emergency Telephone: 1-877-734-7334 – Beacon Lubricants, Inc.

Emergency Telephone: 1-800-424-9300 (24 hours) – Chemtrec approval

Visit us at: www.beaconlubricants.com

SECTION 2

HAZARDS IDENTIFICATION

This material is hazardous according to regulatory guidelines (M)SDS Section 15)

CLASSIFICATION:

Skin irritation: Category 2. Eye irritation: Category 2A.

LABEL:

Pictogram:



Signal Word: Warning

Hazard Statements:

H315: Causes skin irritation. H319: Causes serious eye irritation.

Precautionary Statements:



P264: Wash skin thoroughly after handling. P273: Avoid release to the environment. P280: Wear protective gloves and eye / face protection. P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing. P332 + P313: If skin irritation occurs: Get medical advice/ attention. P337 + P313L If eye irritation persists: Get medical advice/attention. P362 + P364: Take off contaminated clothing and wash it before reuse. P501: Dispose of contents and container in accordance with local regulations.

Other hazard information:

HAZARD NOT OTHERWISE CLASSIFIED (HNOC): None as defined under 29 CFR 1900.1200.

PHYSICAL / CHEMICAL HAZARDS

No significant hazards

HEALTH HAZARDS

High-pressure injection under skin may cause serious damage. Mists may be irritating to the eyes, nose, throat and lungs. May be irritating to nose, throat, and lungs.

ENVIRONMENTAL HAZARDS

No significant hazards.

NFPA Hazard ID: Health: 2 Flammability: 1 Reactivity: 0

HMS Hazard ID: Health: 2 Flammability: 1 Reactivity: 0

Note: This material should not be used for any other purpose than the indented use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

This material is defined as a mixture.

Hazardous Substance(s) or Complex Substance(s) required for disclosure

Name	CAS#	Concentration*	GHS Hazard Codes



1,2,3-PROPANETRIOL	56-81-5	1 - < 5 %	None
BORIC ACID (H3BO3), COMPOUND WITH 2,2',2''-NITRILOTRIS (ETHANOL)	10049-36-2	20 - < 30 %	H315, H319 (2A)
BORIC ACID, COMPOUND WITH 2- AMINOETHANOL	26038-87-9	5 - < 10 %	H315, H319 (2A)
PROPYLENE GLYCOL	57-55-6	0.1 - < 1 %	None
SODIUM 2- PYRIDINETHIOL-1- OXIDE	3811-73-2	0.1 < 1 %	H302, H312, H315, H319(2A), H400 (M factor 1)

*All Concentrations are percent by weight unless material is a gas. Gas concentration are in the percent by volume.

As per paragraph (i) of 29 CFR 1910.1200, formulation is a considered a trade secret and specific chemical identity and exact percentage (concentration) of composition may have been withheld. Specific chemical identity and exact percentage composition will be provided to health professionals, employees, or designated representatives in accordance with applicable provisions of paragraph (i).

SECTION 4

FIRST AID MEASURES

INHALATION

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

SKIN CONTACT

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms form high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extend of injury.

EYE CONTACT



Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

First aid is normally not required. Seek medical attention if discomfort occurs.

NOTE TO PHYSICIAN

Pre-existing conditions which may be aggravated by exposure include emphysema and asthma. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION 5

FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Inappropriate Extinguishing Media: Straight streams of water

FIRE FIGHTING

Fire Fighting Instructions: Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water supply to cool fire exposed surfaces and to protect personnel.

Hazardous Combustion Products: Aldehydes, sulfur oxides, Oxides of carbon, Smoke, Fume, Incomplete combustion products.

FLAMMABILITY PROPERTIES

Flash Point [Method]: >100°C (212°F) [ASTEM D-92]

Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D

Autoignition Temperature: >150°C (302°F)

SECTION 6

ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800) 424-8802.



PROTECTIVE MEASURES

Avoid contact with spilled material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Service. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgement of the emergency responders.

SPILL MANAGEMENT

Land Spill: Stop leak if you can do it without risk. Recover by pumping or with suitable absorbent.

Water Spill: Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIRONMENTAL PRECAUTIONS

Remove debris in path of spill prior to oiling and remove contaminated debris from shoreline and water surface and dispose of according to local regulations. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

SECTION 7

HANDLING AND STORAGE

HANDLING

Avoid breathing mists or vapors. Avoid contact with skin. Avoid contact with eyes. Small metal particles from machining may cause abrasion of the skin and may predispose to dermatitis. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or ground procedures. However, bonding and ground may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance.

Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended practice on Static Electricity) or

CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

Static Accumulator: This material is a static accumulator.

STORAGE:

The container choice, for example storage vessel, may effect static accumulation and dissipation. Do not store in open or unlabeled containers. Keep away from incompatible materials.

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Substance Name	Form	Limit / Standard		Note	Source
1,2,3-PROPANETRIOL	Respirable fraction.	TWA	5mg/m ³	N/A	OSHA Z1
1,2,3-PROPANETRIOL	Total Dust.	TWA	15 mg/m ³	N/A	OSHA Z1
PROPYENE GLYCOL	Aerosol.	TWA	10 mg/m ³	N/A	AIHA WHEEL

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

No biological limits allocated.

ENGINEERING CONTROLS

The level of protection and toes of controls necessary will vary depending upon potential exposure conditions.

Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information of the selection of protective equipment for use with this

material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: Particulate air-purifying respirator approved for dust / oil mist is recommended.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filters capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include: Chemical resistant gloves are recommended

Eye Protection: Chemical goggles are recommended

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include: Chemical/oil resistant clothing is recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Environmental Controls

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.



Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the supplier for additional information.

GENERAL INFORMATION

Physical State: Liquid

Color: Blue

Odor: Characteristic

Odor Threshold: N/D

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 15°C): 1.1

Flammability (Solid, Gas): N/A

Flash Point [Method]: >100°C (212°F) [ASTM D-92]

Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D

Autoignition Temperature: >150°C (302°F)

Boiling Point / Range: >100°C (212°F)

Decomposition Temperature: N/D

Vapor Density (Air = 1): N/D

Vapor Pressure: < 0.013 kPa (0.1 mm Hg) at 20 °C [ESTIMATED]

Evaporation Rate (n-butyl acetate = 1): < 1

pH: 9.4

Log Pow (n-Octanol/Water Partition Coefficient): N/D

Solubility in Water: EMULSIFIES

Viscosity: 17 cSt (17 mm²/sec) at 40°C

Oxidizing Properties: See Hazards Identification Section.

OTHER INFORMATION

Freezing Point: N/D

Melting Point: N/A

Pour Point: < 0°C (32°F)

SECTION 10

STABILITY AND REACTIVITY

REACTIVITY: See sub-sections below.

STABILITY: Material is stable under normal conditions

CONDITIONS TO AVOID: Excessive heat. High energy sources of ignition.

MATERIALS TO AVOID: Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization will not occur.

SECTION 11
TOXICOLOGICAL INFORMATION
INFORMATION ON TOXICOLOGICAL EFFECTS

Hazard Class	Conclusion / Remarks
Inhalation	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on the assessment of the components.
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures.
Ingestion	
Acute Toxicity: No end point date for material	Minimally Toxic. Based on assessment of components.
Skin	
Acute Toxicity: No end point date for material	Minimally Toxic. Based on assessment of components.
Skin Corrosion/Irritation: No end point data for material.	Negligible irritation to skin at ambient temperatures. Based on assessment of the components.
Eye	
Serious Eye Damage/Irritation: No end point data for material	May cause mild, short-lasting discomfort to eyes. Based on assessment of components.
Sensitization	
Respiratory Sensitization: No end point data for material	Not expected to be a respiratory sensitizer
Skin Sensitization: No end point date for material	Not expected to be a skin sensitizer. Based on assessment of the components.
Aspiration: Data available	Not expected to be an aspiration hazard. Based on phsico-chemical properties of the materials.
Germ Cell Mutagenicity: No end point data for material	Not expected to be a germ cell mutagen. Based on assessment of

	the components.
Carcinogenicity: No end point data for material	Not expected to cause cancer. Based on assessment of the components.
Reproductive Toxicity: No end point data for material	Not expected to be a reproductive toxicant. Based on the assessment of the components
Lactation: No end point data for material	Not expected to cause harm to breast-fed children
Specific Target Organ Toxicity (STOT)	
Single Exposure: No end point data for material	Not expected to cause organ damage from a single exposure
Repeated Exposure: No end point data for material	Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components.

TOXICITY FOR SUBSTANCES

NAME	ACUTE TOXICITY
SODIUM 2-PYRINDINETHIOL-1-OXIDE	Dermal Lethality: LD50 1800 mg/kg (Rabbit); Inhalation Lethality: 4 hour(s) LC50 1.08 mg/l (Aerosol) (Rat); Oral Lethality: LD50 1208 mg/kg (Rat)

OTHER INFORMATION

For the product itself: Synthetic base oils: Not expected to cause significant health effects under conditions of normal use, based on laboratory studies with the same or similar materials. Not mutagenic or genotoxic. Not sensitizing in test animals and humans.

The following ingredients are cited on the lists below: None.

--REGULATORY LISTS SEARCHED--

1 = NTP CARC 3 = IARC 1 5 = IARC 2B
2 = NTP SUS 4 = IARC 2A 6 = OSHA CARC



The information given is based on data available for the material, the components of the material, and similar materials.

ECOTOXICITY

Material — Not expected to be harmful to aquatic organisms.

MOBILITY

Components — Expected to remain in water or migrate through soil.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

Base Oil Components— Expected to be inherently biodegradable

BIOACCUMULATION POTENTIAL

Components — Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bio concentration or limit bioavailability

SECTION 13

DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance current applicable laws and regulations, and material characteristics at time of disposal.

DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

REGULATORY DISPOSAL INFORMATION

RCRA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

Empty Container Warning: Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with



governmental regulations. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJUST OR DEATH.

SECTION 14

TRANSPORT INFORMATION

LAND (DOT): Not Regulated for Land Transport

LAND (TDG): Not Regulated for Land Transport

SEA (IMDG): Not Regulated for Sea Transport according to IMDG-Code

Marine Pollutant: No

AIR (IATA): Not Regulated for Air Transport

SECTION 15

REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD: This material is considered hazardous in accordance with OSHA HazCom 2012, 29, CFR 1910. 1200.

Complies with the following national/regional chemical inventory requirements: AICS, DSL, ENCS, IECSC, KECI, TSCA

PRODUCT REGISTRATION STATUS: USA

EPCRA SECTION 302: This material contains no extremely hazards substances.

CWA / OPA: This product is classified as an oil under Section 311 of the Clean Water Act (40 CFR 110) and the Oil Pollution Act of 1990. Discharge or spills which produce a visible sheen on either surface water, or in waterway/sewers which lead to surface water, must be reported to the Nation Response Center at 800-424-8802

SARA (311/312) REPORTABLE HAZARD CATEGORIES: Immediate Health

SARA (313) TOXIC RELEASE INVENTORY: This material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

The following ingredients are cited on the lists below:



P.O. Box 754,
Edinboro, PA 16412-0754

sales@beaconlubricants.com

toll free: (877) 734-7334

phone: (814) 734-7535

fax: (814) 734-3460

safety data sheet

Chemical Name	CAS Number	List Citations
1,2,3-PROPANETRIOL	56-81-5	4, 13, 16, 17, 18
PROPYLENE GLYCOL	57-55-6	16, 17

--REGULATORY LISTS SEARCHED--

1 = ACGIH ALL 6 = TSCA 5a2 11 = CA P65 REPRO 16 = MN RTK

2 = ACGIH A1 7 = TSCA 5e 12 = CA RTK 17 = NJ RTK

3 = ACGIH A2 8 = TSCA 6 13 = IL RTK 18 = PA RTK

4 = OSHA Z 9 = TSCA 12b 14 = LA RTK 19 = RI RTK

5 = TSCA 4 10 = CA P6 CARC 15 = MI 293

Code Key: CARC=Carcinogen; REPRO=Reproductive

SECTION 16

OTHER INFORMATION

N/D = Not determined, N/A = Not applicable

KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

- H302: Harmful if swallowed; Acute Tox Oral, Cat 4
- H312: Harmful in contact with skin; Acute Tox Dermal, Cat 4
- H315: Causes skin irritation; Skin Corr/Irritation, Cat 2
- H319(2A): Causes serious eye irritation; Serious Eye Damage/Irr Cat 2A
- H400: Very toxic to aquatic life; Acute Env Tox, Cat 1

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Updates made in accordance with implementations of GHS requirements. The information and recommendations contained herein are, to the best of Beacon Lubricants knowledge and belief, accurate and reliable as of the date issued. You can contact Beacon Lubricants to insure that this document is the most current available from Beacon Lubricants. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for intended use. If the buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted.