

20' HALF HEIGHT- SIDE SWING DOOR OFFSHORE BASKET

20' x 8' x 4'2"

Side Swing Door

Hot Dip Galvanized or Painted Finish

CERTIFICATIONS

DNV 2.7-1 (DNVGL-ST-E271) Standard for Offshore Containers

ISO 10855 International Standard for Offshore Containers and associated lifting sets

In support of IMO MSC Circ 860

CSC Convention for Safe Containers


API / Shell OPS0055 by request

Classification Society : Lloyd's Register or Det Norske Veritas (DNV)



DIMENSIONS (+/- 1/4")

	EXTERNAL		INTERNAL
Length	6058 mm 20'		5862 mm 19'-2 25/32"
Width	2438 mm 8'		2194 mm 7'-2 3/8"
Height	1280 mm 4'-2 25/64"		942 mm 3'-1 5/64"
Door Opening Width			2270 mm 7'-5 23/64"
Internal Cubic Capacity			12.2 M ³ 431 FT ³



RATINGS (+/- 3%)

For Offshore / Sling Movement

Max Gross Weight	12,550 kg	27,620 lbs
Max Payload	10,000 kg	22,050 lbs
Tare Weight	2,550 kg	5,620 lbs

For Standard Cargo / Forklift Lift Movement

Max Gross Weight	20,000 kg	44,090 lbs
Max Payload	17,450 kg	38,470 lbs
Tare Weight	2,550 kg	5,620 lbs



INCLUDES

- DNV Certified Wire Rope Lifting Sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

