

ProBuilder™ 36 Clean Face Collection

TRADITIONAL GAS FIREPLACE

FIREPLACE
XTRODINAIR
FIREPLACEX.COM



The ProBuilder 36 Clean Face GSB is shown with the Black Glass Fireback, 8 Piece Basic Oak Log Set, and optional Ember-Glo™

The ProBuilder 36 Clean Face is our mid-sized model that is ideal for providing zonal warmth to individual rooms in the home, such as family rooms and offices. The tall dancing flames and elegant “clean face” appearance of this fireplace will add both beauty and warmth to any living space. This Deluxe model includes enhanced performance features and aesthetic choices, such as the GreenSmart® Remote Control, Ember-Glo™, a 180 CFM convection fan and two log set options.

- Heating Capacity*: Up to 1,150 Sq. Ft.
- BTU/Hr Input: MV/GSB: 13,000 to 25,000 NG (48% turndown)
12,000 to 24,000 LP (50% turndown)
Deluxe: 5,000 to 25,000 NG (80% turndown)
6,000 to 24,000 LP (75% turndown)
- P4 Efficiency: MV: 73.77% NG, 75.33% LP
GSB: 74.78% NG, 76.41% LP
Deluxe: 75.75% NG, 77.43% LP
- Steady State Efficiency: MV/GSB: Up to 82.66% NG, 84.06% LP
Deluxe: Up to 83.81% NG, 85.88% LP
- Weight: 170 lbs. (77 kg).
- Viewing Area: Tempered Glass: 30-1/8" W x 26-1/8" H (785 sq. in.)

*Heating capacity will vary with floor plan, insulation, and outside temperature

AVAILABLE THREE VERSIONS:

- MV Model
On Demand Standing Pilot
- GSB Model
GreenSmart® Basic, Electric Ignition, Basic Remote
- Deluxe Model includes enhanced performance features and aesthetic choices, such as the GreenSmart® Remote Control, Ember-Glo™, and a 180 CFM convection fan.

ProBuilder™ 36 Clean Face Collection

TRADITIONAL GAS FIREPLACE



Standard Features MV & GSB Models

Features an economical electronic ignition system.

- Continuous Pilot or Basic GreenSmart® Ignition Modes
- Choice of Logs: Basic Oak, High-Definition Oak or High-Definition Birch
- 110 V Power Required, Built-in Automatic Battery Backup
- ON/OFF Wall Switch
- Easy Access Controls

Standard Features Deluxe Models

Includes a combination of incredible exclusive features.

- Continuous Pilot or GreenSmart® Ignition Modes
- Choice of Logs: High-Definition Oak or High-Definition Birch
- 110 V Power Required, Built-in Automatic Battery Backup
- Ember-Glo™ Halogen Under-lit Accent Lighting
- All Functions Are Controlled From the GreenSmart® Remote
- 180 CFM Variable Speed Convection Fan

Optional Accessories for MV & GSB Models

Basic GreenSmart® Wireless Thermostat Remote Control

- Manual Setting - ON/OFF controls.
- Thermostat Setting - Fireplace turns ON/OFF to maintain your desired home/room temperature.

Convection Fan

Variable speed 180 CFM* fan helps increase the natural convection of heated air into the room as it circulates around the firebox and glass frame. The fan speed is manually controlled by a rheostat dial.

*Cubic Feet Per Minute

Wired Wall Timer

The wired wall timer allows you to set the shut off time of your fireplace in 30 minute increments with a two hour maximum time limit.

Ember-Glo™

Ember-Glo™ combines adjustable halogen under-lighting with colored glass and embers to provide an amazingly realistic ember bed effect. ON/OFF and brightness are controlled manually with a rheostat dial.

Standard GreenSmart® Multi-Function Wireless Thermostat Remote Control



- Thermostat and Smart Thermostat Modes
- Flame Adjustment (6 Levels)
- Change Between GreenSmart® and Continuous Pilot Modes
- Fan Operation
- Ember-Glo™ ON/OFF
- Comfort Control™ ON/OFF

CoolSmart TV Wall™

Our optional CoolSmart TV Wall™ Kit allows you to safely install a television above your gas fireplace (either recessed or mounted), without requiring a mantel.



Scan For Manual

Optional Log Sets for MV, GSB, and Deluxe Models

8 Piece Basic Oak
MV/GSB Only



High Definition
10 Piece Classic Oak



High Definition
10 Piece Birch



Optional Firebacks

Personalize the inside of your fireplace



Common Brick Fireback



High Gloss Black Glass Fireback