

10' STANDARD OFFSHORE CONTAINER

10' x 8' x 8'6" Standard Height - Corrugated Panel
 Double Cargo Doors on one end
 Hot Dip Galvanized or Painted Finish
 Optional Removable Shelf



CERTIFICATIONS

DNV 2.7-1 (DNV-ST-E271) Standard for Offshore Containers
 ISO 10855 International Standard for Offshore Containers and associated lifting sets
 In support of IMO MSC Circ 860
 CSC Convention for Safe Containers
 API / Shell OPS0055 by request
 Classification Society : Lloyd's Register (LR) or Det Norske Veritas (DNV)

DIMENSIONS (+/- 1/4")

| | EXTERNAL | INTERNAL |
|-------------------------|---------------------|---|
| Length | 2991 mm 9' - 9 3/4" | 2802 mm 9' - 2 5/16" |
| Width | 2438 mm 8' | 2288 mm 7' - 6 5/64" |
| Height | 2591 mm 8' - 6" | 2238 mm 7' - 4 7/64" |
| Door Opening Width | | 2258 mm 7' - 4 57/64" |
| Door Opening Height | | 2253 mm 7' - 4 11/16" |
| Internal Cubic Capacity | | 14.3 M ³ 505 FT ³ |



RATINGS (+/- 3%)

For Offshore / Sling Movement

| | | |
|------------------|-----------|------------|
| Max Gross Weight | 10,000 kg | 22,050 lbs |
| Max Payload | 7,800 kg | 17,200 lbs |
| Tare Weight | 2,200 kg | 4,850 lbs |

For Standard Cargo / Fork Lift Movement

| | | |
|------------------|-----------|------------|
| Max Gross Weight | 10,000 kg | 22,050 lbs |
| Max Payload | 7,800 kg | 17,200 lbs |
| Tare Weight | 2,200 kg | 4,850 lbs |

INCLUDES

- DNV Certified Wire Rope Lifting Sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

