

36 Elite NexGen-Hybrid™

WOOD FIREPLACE



The 36 Elite NexGen-Hybrid™ combines elegant style with high performance heat to bring you an excellent home heater for large spaces up to 2,500 square feet. This wood burning fireplace features NexGen-Hybrid™ technology, which produces cleaner, longer burns, higher efficiencies, and more heat into your home.

Key features you'll love about the 36 Elite NexGen-Hybrid™ fireplace:

- Huge 3.13 cubic foot firebox accommodates logs up to 24 inches in length
 - Large ceramic glass viewing area gives you a great view of the fire from anywhere in the room
 - Charming arched door replicates the look of a traditional masonry fireplace and complements all styles
 - Long burn times, up to 12 hours
 - Bypass damper helps to prevent smoke-backs during loading and reloading
 - Posi-Pressure technology evenly distributes heat throughout your home
-

36 Elite NexGen-Hybrid™

WOOD FIREPLACE



Classic Arch™ black double door



Classic Arch™ black single door



Artisan™ single door

Heating Capacity*:	Up to 2,500 square feet*
Maximum Burn Time:	Up to 12 hours
Log Length:	24"
EPA Tested BTU Range**:	10,733 to 47,514 BTUs/Hr.
Cord Wood Tested BTUs:	17,500 to 70,000 BTUs/Hr.
Emissions:	0.6 grams/particulate per hour (Crib Wood)
Efficiency:***	79.5% HHV
Firebox:	3.13 cubic feet
Glass Viewing Area:	Ceramic Glass, Double Door: 11-1/4" W x 14-1/2" H (each side), 300.6 Sq. In. Ceramic Glass, Single Door: 25-1/4" W x 14-1/2" H, 319.7 Sq. In.

* Heating capacity may vary depending on degree of home insulation, floor plan and ambient temperature zone of the area you live.

** EPA tests to determine BTU output are achieved with a single load of wood at each burn rate. At home, you are likely to add more wood to your stove to maintain your desired comfort level. By the simple process of loading your stove with additional wood, you could achieve up to a 20% higher heat output than established during EPA testing.

***This heater meets the 2020 U.S. EPA's crib wood emission limits for wood heaters. Tested to EPA ASTM E2780-10, ASTM 2515-10, CSA B415.1-10.

Scan For
Manual



Fireplace Xtrordinaire® Wood Burning Fireplaces are protected by one or more of the following patents: U.S. 9,170,025, 4,665,889 as well as other U.S. and Foreign Patents pending. Fireplace Xtrordinaire® reserves the right to alter or improve its products at any time without notification. All trademarks belong to Travis Industries, Inc. For installation specifications refer to the Owner's Manual found on the Fireplace Xtrordinaire® website.
© Copyright T. I. 01/2026 Printed in the U.S.A. 98801117