

Vans Rules:

Rule questions call Greg at 217-714-9997. No calls after 7pm.

VAN PREP:

- Front wheel drive only.
- Sedagons on pre rans.
- All vans must be completely stripped.
- Seat belts are required.
- Battery may be moved but must be secure and covered in the van.
- No painting or undercoating the frame.

GAS TANK:

- Stock gas tank needs to be removed.
- All gas tanks need to be steel or aluminum.
- Electric fuel pumps are allowed. Must be covered with nonflammable material.

RADIATOR AND CORE SUPPORT:

- Radiator, core support and factory mount cannot be moved.
- Factory condenser or $\frac{1}{8}$ " expanded metal / rad guard only. May be bolted in with (4)- 3/8 bolts and cannot be used for reinforcement at all.
- 1" max threaded rod through the front sub mount / frame hole with a max of 4 nuts per threaded rod. No welding allowed.

BODY:

- No body seams welds.
- Doors may be wired shut via sheet metal in 8 locations per door. May also weld doors in 8 locations with 3x3 plate.
- Unlimited 9 wire other than hood and rear hatch.

HOOD AND HATCH:

- Hood needs to be open for inspection.
- Hoods must have two 2 holes, at least four 4" in diameter on each side of the hood. 8 total $\frac{3}{8}$ " bolts may be used to hold sheet metal together around cut outs in hood.
- 6 total spots of #9 wire to secure the hood down.

- Hatch must be wired shut in 8 locations with 2 loops of wire each.

SAFETY CAGE:

- All vans must have a 4-point cage. No kickers. 4" off van floor. 60" max length side bars.
- May have 4 vertical down legs 2"x4" tube. 2 per side.
- Cage can be 4" square tubing, or 4"x 6" tube.
- Tank protector 24"x24" allowed and centered on the rear.
- (2) 3"x ¼" max windshield straps or wire required, bolted or welded.

FRAMES/SUSPENSION:

- Fresh- can have 2 total 6'x6' ¼ plates. Your choice of placement. Plates and welds cannot touch each other or the bumper strap.
- Pre ran- can add 4 more 6x6x ¼" plates for a total of 6. They cannot touch each other.
- All steering / suspension components must remain OEM style stock.
- Stock or aftermarket solid suspension allowed.

BUMPERS:

- Can use a car or homemade bumper. No spears.
- Bumpers may be loaded.
- Pointies can be a max. of 8" from the front side of the bumper and need to have a min. of 26" wide taper.
- 4"x4" max tube 8" long welded to connect the rail to the bumper.
- Bottom of the front bumper needs to be 22" off the ground.
- #9 wire from the front bumper to core support in spots.

ENGINE AND TRANSMISSION:

- No distributor protectors or cradles.
- Carb/header protectors are allowed.
- May chain down engine.
- Aftermarket pedals and shifters are allowed

TIRES:

- Any tires and wheels.
- Tires are required.