






1. PATTERN AND REPEAT

2. LAYOUT SUGGESTIONS





SPECIFICATIONS

WOOD TILE CONSTRUCTION:

Engineered wood.

4mm wear layer over 9 ply substrate.

THICKNESS:

5/8 inches.

REPEAT:

N/A

BOX QUANTITY:

21 SF per box. 56 tiles total per box.

COVERAGE PER TILE:

.375 SF per tile.

INSTALLATION:

Glue down. (See installation guidelines) Wood tiles are NOT provided on mesh or panel backing.

USAGE:

Warranted for Commercial or Residential walls & ceilings. Not suitable for areas exposed to running water: inside

Not suitable for outdoor applications.

Not suitable for flooring.

LEADTIME:

6-8 weeks for production.

Expedited options available upon request for an upcharge.

Varies by pattern & wood species. Multiple stain selections do not affect pricing.

FIRE RATING:

Class C. (Class B available upon request)

STAINING SYSTEM:

Rubio Monocoat hard oil finish - no VOC. Available unfinished.

LEED CREDITS:

2009 NC/CI MR Credit 5 - Regional Materials 2009 NC/CI IEQ Credit 4.1-4.4 - Low Emitting Finish

***This product may contribute to the achievement of LEED credits, although |BC makes no guarantees of representation of such

CAD PATTRNS AVAILABLE UPON REQUEST.

Contact your local JBC representative.

3. SPECIES

4. STAINS





Plain White Oak Walnut



Quarter White























AVAILABLE ON WALNUT SPECIES:



Polished Amber



















Black Onyx