

10' TARPED OPEN TOP OFFSHORE CONTAINER

10' x 8' x 8'6" Standard Height
 Double Cargo Doors on one end & Open Top
 Hot Dip Galvanized or Painted Finish



CERTIFICATIONS

DNV 2.7-1 (DNVGL-ST-E271) Standard for Offshore Containers
 ISO 10855 International Standard for Offshore Containers and associated lifting sets
 In support of IMO MSC Circ 860
 CSC Convention for Safe Containers
 API / Shell OPS0055 by request
 Classification Society : Lloyd's Register (LR) or Det Norske Veritas (DNV)

DIMENSIONS (+/- 1/4")

	EXTERNAL		INTERNAL
Length	2991 mm 20'		2781 mm 9' - 1 31/64"
Width	2438 mm 8'		2250 mm 7' - 4 37/64"
Height	2591 mm 8'-6"		2246 mm 7' - 4 27/64"
Door Opening Width			2218 mm 7' - 3 5/16"
Door Opening Height			2192 mm 7' - 2 19/64"
Internal Cubic Capacity			14 M ³ 494 FT ³
Top Opening L x W			2730 x 2194 mm **



RATINGS (+/- 3%)

For Offshore / Sling Movement

Max Gross Weight	10,000 kg	22,050 lbs
Max Payload	7,750 kg	17,090 lbs
Tare Weight	2,250 kg	4,960 lbs

For Standard Cargo / Fork Lift / Top Lift Movement

Max Gross Weight	10,000 kg	22,050 lbs
Max Payload	7,750 kg	17,090 lbs
Tare Weight	2,250 kg	4,960 lbs

INCLUDES

- DNV Certified Wire Rope Lifting Sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

