

20' DOUBLE DOOR OFFSHORE CONTAINER

20' x 8' x 8'6" Standard Height - Flat Panel

Double Cargo Doors on both ends

Hot Dip Galvanized or Painted Finish



CERTIFICATIONS

DNV 2.7-1 (DNV-ST-E271) Standard for Offshore Containers

ISO 10855 International Standard for Offshore Containers and associated lifting sets

In support of IMO MSC Circ 860

CSC Convention for Safe Containers

API / Shell OPS0055 by request

Classification Society : Lloyd's Register (LR) or Det Norske Veritas (DNV)

DIMENSIONS (+/- 1/4")

	EXTERNAL	INTERNAL
Length	6058 mm 20'	5848 mm 19' - 2 15/64"
Width	2438 mm 8'	2218 mm 7' - 3 5/16"
Height	2591 mm 8' - 6"	2218 mm 7' - 3 5/16"
Door Opening Width		2218 mm 7' - 3 5/16"
Door Opening Height		2198 mm 7' - 2 9/16"
Internal Cubic Capacity		28.8 M ³ 1017 FT ³



RATINGS (+/- 3%)

For Offshore / Sling Movement

Max Gross Weight	16,500 kg	36,375 lbs
Max Payload	12,000 kg	26,455 lbs
Tare Weight	4,500 kg	9,920 lbs

For Standard Cargo / Fork Lift / Top Lift Movement

Max Gross Weight	24,000 kg	52,910 lbs
Max Payload	19,500 kg	42,990 lbs
Tare Weight	4,150 kg	9,150 lbs

INCLUDES

- DNV Certified Wire Rope Lifting Sling
- Full Data Book
- Original Certificates
- Electronic Mobilization Packet
- Delivery to your yard

