



beacon
lubricants INC

P.O. Box 754,
Edinboro, PA 16412-0754
sales@beaconlubricants.com

toll free: (877) 734-7334
phone: (814) 734-7535
fax: (814) 734-3460

technical data sheet

Hydraulic Anti-Wear XL Oils

Product Application:

Beacon Hydraulic Anti-Wear XL Oils are premium, heavy duty, high detergent, ashless "zinc free" fluids developed to meet the requirements of high output hydraulic systems. They are designed for use in high pressure or high-speed vane and gear-type hydraulic pumps, rotary vane-type compressors, machine tools and circulating systems.

They were developed to exceed the exacting specifications of modern hydraulic systems utilizing high pressure, high output pumps while excelling at providing the best lubrication and operating medium for the precise requirements of close tolerance servo-valves and the ultra-precision of computer numerical controlled or "cnc" machines.

Package Size:

Bulk, Drums, Pails

Meets or Exceeds the following Specifications:

Arburg Injection Molding
Bosch Rexroth RDE 90245
Bosch Rexroth RA & RE 90220, 90221
HOCNF Norway - NEMS, Black
Hagglunds-Denison HF-0, HF-1, HF-2
Vickers M-2952-S, 35VQ-25
Cincinnati Machine, P-68, P-69, P-70
US Steel 127, 128
Racine Vane Pumps- Variable Volume

U.S. Fish and Wildlife Aquatic Toxicity LC-50
DIN 51524-2:2017-06
DIN 51524-3:2017-06
ISO L-HM, (ISO 11158, 2009)
Ortlinghaus-Werke GmbH ON 9.2.19
Eaton E-FDGN-TB002-E
Husky
ZF TE-ML 04K
ASTM D6158

Features and Advantages:

- *Environmentally Responsible
- *Ability to maintain proper viscosity at high temperatures
- *Excellent oxidation and rust protection
- *Excellent anti-foaming properties
- *Applications where cross-contamination of hydraulic fluids and coolants can occur
- *Thin oil-film corrosion protection



beacon
lubricants INC

P.O. Box 754,
Edinboro, PA 16412-0754
sales@beaconlubricants.com

toll free: (877) 734-7334
phone: (814) 734-7535
fax: (814) 734-3460

technical data sheet

Typical Characteristics:

ISO Grade	15	22	32	46	56	68	100
Gravity, Degrees API	30.5	30.2	30.1	28.5	28.5	29	28
Viscosity Index (Min.)	95	100	152	150	150	140	138
Viscosity cSt @ 100°C	3.4	4.2	5.4	6.7	7.5	8.2	11
cSt @ 40°C	15	22	32	46	56	67	98
Flash Point, COC, °F	370	400	430	435	435	450	450
Pour Point, °F	-35	-35	-30	-20	-20	-20	-10
Oxidation astm D943	>8000	>8000	>8000	>8000	>8000	>8000	>8000

Product Bench Test

Method

Results

Copper Corrosion	D 130	1B
Steel Corrosion	D 665 A, B	Pass
Demulsibility	D 1401	40-40-0 (15)
Foam Sequence III	D 892	20/0
Thermal Stability	D 2070	
Appearance of Copper Rod		6
Appearance of Steel Rod		2
Sludge, mg./100 ml.		2.8
Hydrolytic Stability	D 2619	
Copper wt. loss, mg./cm ²		0.034
TAN, Water layer		3.7
Filtration	Denison	
Time to filter dry, sec		165
Time to filter, 2% water, sec.		244
Filtration	AFNOR	
Dry, FI		1.08
Wet, FI		1.28
Wear, Four Ball, scar, mm.	D 4172	
Conditions – 40 kg., 1800 rpm, 130 °F, 1hr		0.40

Visit us at www.beaconlubricants.com



beacon
lubricants INC.

P.O. Box 754,
Edinboro, PA 16412-0754

sales@beaconlubricants.com

toll free: (877) 734-7334

phone: (814) 734-7535

fax: (814) 734-3460

technical data sheet

Oxidation, hr.	D 943	7600
Oxidation, 1000 hr	D 4310	
Cu, mg.		10.7
Fe, mg.		<1
Total sludge, mg.		24.6
EP, Four Ball	D 2783	
LWI		33.95
Weld Load, kg.		126